

CONFIGURATION: 2 WAY, FULL RANGE ACTIVE ENCLOSURE

ACOUSTICS

Components: HF 1 x 1"
LF 1 x 10"

Amplifier: Class D - PFC 110 -240V

Frequency Response ± 3 dB: 55 Hz - 18 kHz (4 Preset dependent)

Nominal Dispersion H/V: 90° - 60°

Power Handling: LF 350 W program
HF 80 W program

Max Output dB Spl: 124 dB SPL

Connections: 1 XLR Input
1 XLR For Paralleled Connection
1 VDE power socket

Typical throw: 35 mt



MECHANICAL

Shape: Trapeziodal

Box: 12 mm 9 Ply Phenolic Birch

Paint: Water based technical coat or custom finish

Grills: Powder Coated Steel

Rigging: 5 M10 fly Point

Dimension W x D x H: 30 x 26 x 47

Weight: 17 Kg

Handle: 1

GENERAL NOTES

Compact loudspeaker with high performance able to satisfy all the needs of sound reinforcement for small itinerant systems, musicians, folk groups, sporting and theatrical events.

The uncommon range characteristics make it useful for use even in conditions in which other systems cannot guarantee correct intelligibility at medium distance, without ever bothering those in the immediate vicinity.