

**CONFIGURATION: 2 WAY, FULL RANGE PASSIVE ENCLOSURE**

**ACOUSTICS**

**Components:** HF: 1 x 3" Titanium  
LF: 2 x 12" High performance 4" voice coil

**Nominal Impedance:** 4 Ohm

**Frequency Response  $\pm 3$  dB:** 55 Hz – 18 kHz

**Sensitivity 1w@1m:** 100,5 dB

**Nominal Dispersion H/V:** 60° x 60°

**Power Handling:** 1200 W Average  
2200 W Program

**Recommended amp:** 2700 W

**Max Output:** 136 dB SPL

**Connections:** 2 x Speakon®

**Typical throw:** 80 mt



**MECHANICAL**

**Shape:** Trapeziodal

**Box:** 18 mm 13 Ply Mm Phenolic Birch

**Paint:** Black water based technical coat or custom

**Grills:** Powder Coated Steel

**Rigging:** 3 point aero type quick coupling

**Dimension W x D x H:** 40,8 x 33 x 94,6 cm

**Weight:** 42,5 Kg

**Handle:** 2 each side



**GENERAL NOTES**

Great sound, very high power and huge range; these are the data that characterize this project, created to give the possibility to those who work in the sector to have a PA that is very easy to position and calibrate, saving time for the artistic part of on-road work. Also great as a sidefill or drumfill on large stages, like our entire range, in playing any musical genre.

