

CONFIGURATION: 2 WAY, FULL RANGE PASSIVE ENCLOSURE

**ACOUSTICS**

**Components:** HF: 1 x 1"  
LF: 1 x 12"  
**Nominal Impedance:** 8 Ohm  
**Frequency Response ±3 dB:** 70 Hz – 17 kHz  
**Sensitivity 1w@1m:** 101 dB

**Nominal Dispersion H/V:** 65° x 40°  
**Power Handling:** 450 W Average  
650 W Program  
**Max Output:** 130 dB SPL  
**Connections:** 2 x Speakon®  
**Typical throw:** 60 mt



**MECHANICAL**

**Shape:** Trapeziodal  
**Box:** 18 mm 13 Ply Phenolic Birch  
**Paint:** Black water based technical coat or custom  
**Grills:** Powder Coated Steel  
**Rigging:** 5 point aero type quick coupling  
**Dimension W x D x H:** 38 x 30 x 54 cm  
**Weight:** 22 Kg  
**Handle:** 1

**GENERAL NOTES**

Born like all our systems, from our long experience in the live field, it is the most compact speaker of our production that allows you to compose large complex point source systems that are truly effective, due to the project with truly unique characteristics. In fact, it allows you to create stacks or clusters of several speakers without causing phase distortions or lobations of such amplitude as to make the acoustic set-up difficult.

