

CONFIGURATION: 1 WAY, FULL RANGE PASSIVE ENCLOSURE FOR WALL AND ROOF APPLICATION

ACOUSTICS

Components:	2 x 3" (wide range)
Nominal Impedance:	4 or 16 Ohm
Frequency Response ± 3 dB:	110 Hz – 17 kHz
Sensitivity 1w@1m:	94dB
Nominal Dispersion H/V:	80°
Power Handling:	40 W Average 80 W Program
Recommended amp:	100 W
Max Output:	113 dB SPL
Connections:	Speakon® or clamp
Typical throw:	15 mt



MECHANICAL

Shape:	Trapezoidal with frame
Box:	9 mm 7 Ply Phenolic Birch
Paint:	custom
Grills:	Powder Coated Steel
Rigging:	4 screw hole
Dimension W x D x H:	12,0 x 11,0 x 20,0 cm + frame
Weight:	1,9 Kg
Handle:	none



GENERAL NOTES

We want every sound reinforcement need to be met by our products, so here is a speaker that makes it possible to have beautiful LAN sound even from the ceiling! (and from the wall ...)

Thanks to the high possibility of customization of the finish, it lends itself to being able to serve in every area, from re-exporting to resident exhibitions, and on all occasions when a small and discreet speaker is needed.

