

CONFIGURATION: 1 WAY, FULL RANGE PASSIVE LINE SOURCE ENCLOSURE

### ACOUSTICS

**Components:** 12 x 3" (wide range)

**Nominal Impedance:** 5,5 Ohm

**Frequency Response ±3 dB:** 110 Hz – 17 kHz

**Sensitivity 1w@1m:** 102dB

**Nominal Dispersion H/V:** 90° x 40°

**Power Handling:** 240 W Average

500 W Program

**Recommened matching amp:** 450 W @ 8 ohm

**Max Output:** 129 dB SPL

**Connections:** 3 x Speakon® (2 back 1 bottom)

**Typical throw:** 40 mt



### MECHANICAL

**Shape:** Trapeziodal

**Box:** 9 mm 7 Ply Phenolic Birch

**Paint:** Water based technical coat or custom finish

**Grills:** Powder Coated Steel

**Rigging:** 5 x 10 mm screw hole

**Dimension W x D x H:** 12,0 11,0 x 103 cm

**Weight:** 6,8 Kg

**Handle:** none



### GENERAL NOTES

Passive Column, high acoustic performance, an infinite possibility of use also thanks to five suspension points and connection to all professional clamps available, make this performing line source a perfect work tool to meet the needs of any fixed structure or itinerant.

Also configured with the sub SB112 s (in both passive and active version) and with the LN Distancer, it constitutes an effective, streamlined, efficient and freely orientable system on the horizontal axis.

