

CONFIGURATION: **SUBWOOFER ACTIVE ENCLOSURE**

**ACOUSTICS**

- Components:** 1 x 18" High performance weather protected  
**Amplifier:** Class D - PFC 110 -240V  
**Frequency Response ± 3 dB:** 35 Hz - 115 Hz (4 Preset dependent)  
**Nominal Dispersion H/V:** Omni  
**Power Handling:** 3200 W Program  
**Max Output dB Spl:** 131 dB SPL  
**Connections:** 1 XLR Input  
1 XLR For Paralleled Connection  
1 Powercon  
ETH / USB connection for DSP setup  
Armonia® software



**MECHANICAL**

- Shape:** Parallelepiped  
**Box:** 18 mm 13 Ply Phenolic Birch  
**Paint:** Black water based technical coat or custom  
**Grills:** Powder Coated Steel  
**Rigging:** none  
**Dimension W x D x H:** 52 x 55 x 64  
**Weight:** 43,2 Kg  
**Handle:** 2



**GENERAL NOTES**

Equipped with an innovative Tetracoil® engine, this model guarantees power and beautiful sound for every professional need that requires agility of use and great acoustic performance.  
Deep bass, legendary "note" hold without fluctuations, thrilling power.  
Able to ensure both infrabass and high punch performance, as well as being able to form extremely efficient "cardio" groups, it is the ideal choice for the highly demanding professional.