

CONFIGURATION: **SUBWOOFER PASSIVE ENCLOSURE**

ACOUSTICS

- Components:** 1 x 18" High performance weather protected
- Nominal Impedance:** 8 or 4 Ohm
- Frequency Response ± 3 dB:** 35 Hz – 115 Hz
- Sensitivity 1w@1m:** 96 dB
- Nominal Dispersion H/V:** Omni
- Power Handling:** 1800 W Average
3600 W Program
- Recommended amp:** 4000 W
- Max Output:** 134 dB SPL
- Connections:** 2 x Speakon[®]



MECHANICAL

- Shape:** Regular parallelepiped
- Box:** 18 mm 13 Ply Phenolic Birch
- Paint:** Water based technical coat or custom finish
- Grills:** Powder Coated Steel
- Rigging:** Optional frame kit
- Dimension W x D x H:** 52 x 55 x 64 cm
- Weight:** 41 Kg
- Handle:** 2



GENERAL NOTES

The first of our projects that uses the special 18" loudspeaker with Tetracoil[®] system, absolutely unmatched in order to obtain a high-class performance, necessary for today's high-power reproduction.

The characteristics of the project allow to guarantee both infrabass and max punch performance without smudging.

The configuration of the box allows you to create truly efficient and safe stack and cardioid compositions.

