

CONFIGURATION: 2 WAY, ACTIVE LINE SOURCE SYSTEM

ACOUSTICS

Components: Top: 12 x 3" neodymium wide range speakers
Cabled distancer
Sub: 1 x 12" High performance woofer

Amplifier: Switch mode - PFC 110 -240V ready to drive 1 Sub
+ 2 column mono / stereo mode

Frequency Response ± 3 dB: 40 Hz - 18 kHz (4 Preset dependent)

Nominal Dispersion H/V: 40° x 90°

Power Handling: LF: 1 x 1400 W program
HF: 1 or 2 x 500 W program each column
1 / 2 XLR Input (stereo or mono mode switch)

Connections: 1 Powercon in/out
ETH / USB connection for DSP setup Powersoft
Armonia ® software

Typical throw: 40 m



MECHANICAL

Type: Vertical array

Box: Multi ply Phenolic Birch

Paint: Black water based technical coat or custom

Grills: Powder Coated Steel

Dimension W x D x H: Column: 120 x 110 x 1555 mm
Sub: 375 x 360 x 460 mm

PLUS: Top speaker are orientable differently from the Subwoofer

GENERAL NOTES

This efficient and performing active system is extremely simple to assemble, immediately ready for use and allows you to meet the multiple needs of the conference sector and sound reinforcement for the most diverse occasions, from simple audiovisual support to the amplification of musical groups. It can be easily configured to reproduce mono or stereo signals and, thanks to the four presets that can be recalled from the rear panel of the active sub, offer the ideal contour for any event.

This system also offers the unusual possibility of rotating the column with respect to the sub at will, allowing maximum order and freedom of positioning on stage.

Precise and deep bass, high tonal richness throughout the range and a very high rejection at the feedback, make it the ideal complement for the good success of daily work.

