LAN
HIGH DEFINITION ACOUSTIC SYSTEMS

From Stage Experience, to Stage Solution.. and more!

MOD. **SB10-F**

CONFIGURATION: **SLIM SUBWOOFER PASSIVE ENCLOSURE**

ACOUSTICS



Components:	1 x 10” Dual 4 ohm voice coils, 6 layers total high performance woofer
Nominal Impedance:	8 Ohm
Frequency Response ±3 dB:	50 Hz – 120 Hz
Sensitivity 1w@1m:	86 dB
Nominal Dispersion H/V:	Omni
Power Handling:	250 W Average 500 W Program
Max Output:	115 dB SPL
Connections:	Rear speaker terminal block

MECHANICAL

Shape:	Regular parallelepiped
Box:	12 mm 9 Ply Phenolic Birch
Paint:	Black water based technical coat or custom
Rigging:	Optional back frame kit
Dimension W x D x H:	67,5 x 10,5 x 47,5 cm - Box only 67,5 x 12 x 47,5 cm – box with wall frame
Weight:	11,5 Kg

GENERAL NOTES

Engineered to perfectly complement our LN/NP speaker series and the Flatty system, the SB10-F offers a refined and space-efficient low-end solution for mid-high installations.

With its ultra-compact design, it fits neatly inside a recessed wall niche, blending effortlessly into any architectural setting, flexible installation allows both vertical and horizontal positioning.

The integrated rear frame features precision alignment references and discreet cable management directly from the wall, ensuring a clean and sophisticated result.

LAN AUDIO sas - Laboratory Via Po 44 Trecate (NO) Italy
www.lanaudio.it Dino Manfredda: +39 3355315251 dino@lanaudio.it